

# GBT Observing for October 2010

## Legend

The time is local eastern time. The dates are eastern time zone dates and the number on the far right is the local sidereal date at the start of the day. The dark vertically slanted line marks midnight local sidereal time and the light vertically slanted lines mark 6,12, and 18 hours local sidereal time.

The ~ mark indicates that the telescope has not yet been scheduled. The Se or Setup code refers to system preparation for start of Astronomical observing. PCO refers to Program CheckOuts which are feasibility tests of approved proposals. RCO refers to receiver checkouts. Holidays are indicated by non white background for sid day #.

GBT proposal codes on the graphics schedule have been shortened to their minimum unique length. For example a code of 1A7 is GBT01A-007 while 2B45 would be GBT02B-045. The first number in the shortened code is the year after 2000, the letter represents the trimester (A, B or C) and the last number is a number between 1 and 999. Proposal codes followed by \* and one of 3,5,6,8,A indicates if a prime focus receiver is to be used and the particular one to be used.

09/16/2011

The eastern time at midnight local sidereal time on the first of the month is 00h41m.

Codes	Notes
Ab - 10C15	Urquhart et al
Ad - 10B38	Stairs et al
Ae - 10C33*A	Cherinka and Schulte-Ladbeck
Ag - 10C22	Walker and Johnson
Ah - GLST031123	Camilo et al
Ai - 10A61	Ransom et al
Aj - 10C59	Milam et al
Al - 10A64	Pisano and Radford
Am - 9C35	Shirley et al
Ao - 10A56	Mroczkowski et al
Aq - 10A39	Johnson et al
As - 10B50*8	Gwinn et al
Au - GLST031123*8	Camilo et al
At - 10C35	Minter
Av - 10A25	Greaves
Ac - 10C39	Darling et al
Aw - 10C45	Friesen et al
Tj - Receiver Checkout - Ka	
Ta - Ka Zspectrometer Tests	
Tb - Scal mid freq	
Tc - Receiver Checkout - 1070	
Td - RFI Checkout - 1070	
Tf - Receiver Checkout - X	
Tg - Scal low freq	
Th - RFI Checkout - S	
Ti - RFI Checkout - L	
Tk - RFI Checkout - X	
Tl - Receiver Checkout - MBA	
Tm - KFPA cal measurements	
Tn - PTCS - encoder pointing check	
To - Receiver Checkout - 800	
Tp - RFI Checkout - 800	